

KENAI MUNI (ENA)(PAEN) 0 N UTC-9(-8DT) N60°34.40' W151°14.69'

100 B TPA—See Remarks Class I, ARFF Index A NOTAM FILE ENA

RWY 02L-20R: H7855X150 (ASPH-GRVD) S-75, D-150, 2D-250

PCR 461 F/B/X/U HIRL

RWY 02L: REIL. VASI(V4L)—GA 3.0° TCH 53'. RVR-R Thld dsplcd 280'. Rgt tfc.

RWY 20R: MALSR. VASI(V4L)—GA 3.0° TCH 51'. RVR-T

RWY 02R-20L: 1980X75 (GRVL) No Part 121/Part 380 Ops

RUNWAY DECLARED DISTANCE INFORMATION

RWY 02L:TORA-7855 TODA-7855 ASDA-7855 LDA-7575

RWY 20R:TORA-7855 TODA-7855 ASDA-7575 LDA-7575

SERVICE: S2 **FUEL** 100LL, **JET A** **LGT ACTVT** REIL **Rwy 02L**; VASI **Rwy 02L & 20R**—CTAF. When twr clsd ACTVT and incr instst HIRL **Rwy 02L-20R**—Kenai FSS. When twr clsd ACTVT **MALSR Rwy 20R**—CTAF.

NOISE: Noise abatement proc in efct—amgr. **Rwy 02W** arr and **Rwy 20W** dep make fnl apch and cross wind turns S of beachline unless auth by ATC.

AIRPORT REMARKS: Attended Mon-Fri 1700-0200Z. Birds 10 NM radius spring-fall. Exc wx dvrsn unskd acct over 12,500 lbs 48 hr PPR. TPA: **Rwy 02R-20L** and **Rwy 02W/20W** 500' AGL. Ptns of trml ramp, **Twy G** and **H** not vsb fm ATCT. **Rwy 02R** outlined with cones. **Rwy 20L** outlined with cones. Tsnt and coml tie down slips avbl end of water canal. Tsnt prkg S trml ramp; hel prkg N trml ramp. Lndg fee ovr 4000 lb. **Twy A, B & E** PCN 48; **Twy C** PCN 59; **Twy F** PCN 43; **Twy D, J, K & L** PCN 34. Arpt sand gradation lgr than FAA rcmdld see AC150/5200-30.

AIRPORT MANAGER: 907-283-7951

WEATHER DATA SOURCES: ASOS 133.35 (907) 283-6513. LAWRS. (WX CAM)

COMMUNICATIONS: CTAF 121.3 ATIS 133.35

FSS ENA (KENAI)

KENAI RADIO 121.3 121.5 122.65 243.0 (LAA 121.3 when twr clsd)

④ **ANCHORAGE CENTER APP/DEP CON** 125.7 379.1

TOWER 121.3 (1500-0700Z May 1-Sep 30; 1600-0600Z Oct 1-Apr 30) **GND CON** 118.75

AIRSPACE: CLASS D svc 1500-0700Z May 1-Sep 30, 1600-0600Z Oct 1-Apr 30; other times CLASS E.

RADIO AIDS TO NAVIGATION: NOTAM FILE ENA.

(H) (H) **VOR/DME** 117.6 ENA Chan 123 N60°36.88' W151°11.71' 192° 2.9 NM to fld. 115/19E.

VOR unusable:

348°-015° byd 20 NM

DME unusable:

355°-041° byd 35 NM blo 2,000'

ILS/DME 108.9 I-ENA Chan 26 **Rwy 20R.** Class IE.

COMM/NAV/WEATHER REMARKS: Kenai FSS tcl 283-7211. For a toll free call to Kenai FSS dial 1-866-864-1737. Wx avbl from Kenai twr ATIS or from FSS when Kenai twr clsd.

WATERWAY 02W-20W: 4600X240 (WATER)

WATERWAY 20W: Rgt tfc.

SEAPLANE REMARKS: Waterway 02W-20W clsd to ops Nov-Apr. SPB ctdld by Kenai ATCT durg ops hrs. When Kenai ATCT clsd wx avbl fm Kenai ATIS or Kenai FSS. Water ldg area and twy chnl not vsb fm ATCT.

HELIPAD H1: H55X55 (ASPH)

HELIPAD H2: H55X55 (ASPH)

