

HILO INTL (ITO)(PHTO) 2 E UTC-10 N19°43.22' W155°02.91'

HAWAIIAN ISLANDS

38 B LRA ARFF Index—See Remarks NOTAM FILE ITO

P-1C, 2H

RWY 08-26: H9803X150 (ASPH-GRVD) S-99, D-154, 2D-275 PCR 390 F/B/X/T HIRL

IAP

RWY 08: ODALS. PAPI(P4R)—GA 3.0° TCH 71'. Tree.

RWY 26: MALSR. PAPI(P4L)—GA 2.6° TCH 70'. Tree.

RWY 03-21: H5601X150 (ASPH-GRVD) S-52, D-83, 2D-148 PCR 180 F/B/X/T MIRL

RWY 03: REIL. VASI(V4L)—GA 3.25° TCH 48'. Thld dsplcd 351'. Fence.

RWY 21: Pole.

RUNWAY DECLARED DISTANCE INFORMATION

RWY 03: TORA-5192 TODA-5192 ASDA-5601 LDA-5250

RWY 08: TORA-9803 TODA-9803 ASDA-9803 LDA-9803

RWY 21: TORA-5250 TODA-5250 ASDA-5510 LDA-5510

RWY 26: TORA-9803 TODA-9803 ASDA-9803 LDA-9803

SERVICE: S1 **FUEL** 100LL, JET A, A+, MOGAS **LGT** ACTIVATE MIRL Rwy 3-21, HIRL Rwy 08-26, MALSR Rwy 26 and ODALS Rwy 08-118.1. Rwy 08 PAPI unusable byd 3 NM.

NOISE: Avoid overflight of noise sensitive residential areas north, west and southwest of arpt.

AIRPORT REMARKS: Attended 1700-0630Z. Be alert—occasional bird flocks on arpt and in flight across Rwy 08-26 and Rwy 03-21. Twy E btn Twy A and Rwy 08-26 ponding drg hvy rains. For fuel advance notice required, for 100LL call 808 960-5146 or ctc freq 128.95, for JET A call 808-934-7757 or ctc freq 130.8. Class I, ARFF Index C. ARFF avbl 24 hrs, contact 118.1 or 808-961-9317. The 1325' paved area at approach end Rwy 08 marked by chevrons not usable for landing, takeoff, overrun or stopway and cannot be used in computing takeoff data for Rwy 08-26. Obstruction lighted 181' smoke stack located 1/2 mile south of field. Rws 08, 21 and 26 wind cones are lctd in the ROFA. Tower controls entry/exit traffic on taxiways F and E to east terminal ramp. Division 1.1, 1.2, 1.3 explosives prohibited. PPR from arpt manager for transportation of Division 1.4 explosives and hazardous material in or out of arpt. PPR from arpt manager for transient parking. SAID in use. Operate transponders with altitude reporting mode and ADS-B (if equipped) enabled on all airport surfaces. Customs available. Jet fuel available Mon-Sat 1800-0300Z call 808 935-6881/6122 or 961-6601. No mkd pad, hel oper fm FBO hanger area. NOTE: See Area Notices—General Information On Flying To Hawaii.

AIRPORT MANAGER: 808-961-9300

WEATHER DATA SOURCES: ASOS (808) 825-4702

COMMUNICATIONS: CTAF 118.1 ATIS 126.4

® **HILO APP/DEP CON** 119.7 (1600-0800Z)

® **HCF APPROACH APP/DEP CON** 118.45 (0800-1600Z) 284.6

TOWER 118.1 (1600-0800Z) **GND CON** 121.9 **CLNC DEL** 120.25

CLEARANCE DELIVERY PHONE: For CD when ATCT is clsd ctc Honolulu Control Facility at 808-840-6262.

AIRSPACE: CLASS D svc 1600-0800Z; other times CLASS E.

RADIO AIDS TO NAVIGATION: NOTAM FILE ITO.

(H) (H) **VORTAC** 116.9 ITO Chan 116 N19°43.28' W155°00.66' 257° 2.1 NM to fld. 23/11E.

ILS/DME 110.7 I-ITO Chan 44 Rwy 26. Class IA. Unmonitored when ATCT clsd.

KAMUELA N19°59.88' W155°40.19' NOTAM FILE MUE.

HAWAIIAN--MARIANA

(H) (H) **VORW/DME** 113.3 MUE Chan 80 2670/11E.

P-2H

VOR portion unusable:

001°-030° byd 10 NM blo 6,000'

070°-084° byd 25 NM blo 7,000'

070°-084° byd 35 NM blo 13,000'

085°-210° byd 15 NM blo 15,500'

290°-360° byd 10 NM blo 7,500'

290°-360° byd 20 NM blo 16,000'

DME unusable:

070°-084° byd 25 NM blo 7,000'

070°-084° byd 35 NM blo 13,000'

085°-210° byd 15 NM blo 15,500'

290°-030° byd 10 NM

PAHOA N19°32.47' W154°58.33' NOTAM FILE ITO.

HAWAIIAN--MARIANA

NDB (HW) 332 POA 495/11E. NDB unmonitored when ATCT closed.

P-2H