
FORT WORTH MEACHAM INTL (FTW)(KFTW) 5 N UTC-6(-5DT) N32°49.19' W97°21.75' **DALLAS-FT WORTH**
 710 B TPA—See Remarks ARFF Index—See Remarks NOTAM FILE FTW **COPTER**
RWY 16-34: H7502X150 (CONC-GRVD) S-80, D-100, 2S-127, 2D-190, 2D/2D2-350 **H-6H, L-17C, A**
 PCR 310 R/C/W/T HIRL 0.5% up N **IAP, AD**
RWY 16: MALSR. PAPI(P4R)—GA 3.0° TCH 59'. RVR-T Pole.
RWY 34: MALSR. RVR-R Rgt ttc.
RWY 17-35: H4005X75 (ASPH) S-25, D-45 PCR 100 F/C/X/T MIRL No Part 121/Part 380 Ops
RWY 17: PAPI(P2L)—GA 3.75° TCH 56'. Berm. Rgt ttc.
RWY 35: PAPI(P2L)—GA 3.25° TCH 43'.
RUNWAY DECLARED DISTANCE INFORMATION
RWY 16: TORA-7502 TODA-7502 ASDA-7502 LDA-7502
RWY 34: TORA-7502 TODA-7502 ASDA-7306 LDA-7306
SERVICE: S4 **FUEL** 100LL, JET A, A1+ **OX** 1, 3 **LGT** Rwy 17-35 LED lgt can appr brgr than Rwy 16-34; ensure cor rwy
 alnmt.
AIRPORT REMARKS: Attended continuously. Birds on and invof arpt. Rwy 09-27 CLOSED indef. Class IV, ARFF Index A. ARFF
 Index B avbl all users with PPR. Helo skidding opns prohibited on Rwy 17-35. SAID in use. Operate transponders with
 altitude reporting mode and ADS-B (if equipped) enabled on all airport surfaces. If skidding is rqrd, coord with ATCT to
 use Twy B. Twys B, B1, C and D west of Rwy 16-34, Twys C and M east of Twy A, Twys H, J, K south of Twy D, Twy G
 SE of Twy K clsd to air carrier acft with more than 30 psgr seats. Rwy 17-35 designed for acft with wingspan of 49 ft or
 less. Twys B and B1 designed for acft with wingspan less than 79 ft. Rwy 16-34 and Twys A, A1, and M designed for
 acft with wingspan less than 171 ft. All other Twys designed for acft with wingspan of less than 118 ft. Mkd US Customs
 pkg southeast of Txl G and Txl N intxn. PPR for ACR opns with more than 30 psgr seats-24 hr notice rqrd-call Arpt Ops
 817-994-0653. TPA—Rwy 17-35 R/W 1300(590) , F/W 1500(790) , Rwy 16-34 1500(790) , Jets 2000(1290) .
 Arpt fees for use of cust svcs will be could imt upon ldg by city of Fort Worth Arpt opns psnl. User fee arpt. NOTE: See
 Special Notices—Arrival Alert.
AIRPORT MANAGER: 817 392-5400
WEATHER DATA SOURCES: ASOS (817) 740-3346
COMMUNICATIONS: ATIS 120.7
® LONE STAR APP/DEP CON 118.1 (North) 135.975 (South)
MEACHAM TOWER 118.3 **GND CON** 121.9 **CLNC DEL** 124.65
AIRSPACE: CLASS D.
VOR TEST FACILITY (VOT) 108.2
RADIO AIDS TO NAVIGATION: NOTAM FILE FTW.
RANGER (VH) (H) VORTACW 115.7 **FUZ** Chan 104 N32°53.37' W97°10.77' 240° 10.1 NM to fld. 639/6E.
 VOR unusable:
 275°-290° byd 40 NM
 317°-327° byd 40 NM
MUFIN NDB (LOMW) 365 FT N32°53.59' W97°22.40' 165° 4.4 NM to fld. 744/8E.
ILS/DME 109.9 I-FTW Chan 36 Rwy 16. Class IT. LOM MUFIN NDB. DME also serves Rwy 34.
ILS/DME 109.9 I-UXT Chan 36 Rwy 34. Class IB. DME also serves Rwy 16.
 • • • • • • • • • • • • • • • • • •
HELIPAD H1: H35X35 (CONC)
HELIPAD H2: H35X35 (CONC)
HELIPORT REMARKS: H1 and H2 helipads are VMC dalgt use only; non-movement area. Hls repositioning byd imt pkg apron
 and under their own pwr must ctc ATC.
