CONTINUED FROM PRECEDING PAGE

AIRSPACE: CLASS D svc continuous.
RADIO AIDS TO NAVIGATION: NOTAM FILE MCF.
(L) TACAN Chan 47 MCF (111.0) N27º51.67´ W82º30.81´ at fld. 12/6W.
mp 0900–2300Z‡ Fri
TACAN AZIMUTH unusable:
230º–240º byd 30.0 NM
240º–245º byd 30 NM
246º–341º byd 35 NM
342º–345º
346º–011º byd 35 NM
DME unusable:
230º–240º byd 30 NM
241º–284º byd 35 NM
296º–345º byd 35 NM
342º–345º byd 32 NM
346º–011º byd 35 NM
ILS 109.5 I–MCF Rwy 05. Class IC. ILS – 05: Rwy 05 course line is offset 2.9º to SE, rwy hdg is 046 deg. Rwy 23 course line is offset 2.7º to NE, rwy hdg is 226º. MP 1200–1500Z‡ Tue and Thurs.
ILS 111.7 I–GBZ Rwy 23. Class IB. Rwy 23 course line is offset 2.7º to NE, rwy hdg is 226º. MP 1200–1500Z‡ Tue–Wed.
COMM/NAV/WEATHER REMARKS: MacDill surveillance radar provided by Tampa. Tsnt aircrews may ctc 9 OWS for WX BRIEF—DSN 965–0939.

• • • • • • • • • • • • • • • • • • •

HELIPAD H1: H100X100 (CONC)

MANATEE (See PALMETTO on page 158)

MARATHON

THE FLORIDA KEYS MARATHON INTL (MTH)(KMTH) 3 E UTC–5(–4DT) N24º43.58´ W81º03.08´ **MIAMI**
7 B ARFF Index—See Remarks NOTAM FILE MTH **H–8I, L–23C**
RWY 07–25: H5008X100 (ASPH–GRVD) S–62, D–100, 2D–182 PCR 200 F/A/X/T MIRL **IAP, AD**
RWY 07: REIL. PAPI(P4L)—GA 3.0º TCH 25´. Tree.
RWY 25: PAPI(P4L)—GA 3.0º TCH 26´. Tree.
RUNWAY DECLARED DISTANCE INFORMATION
RWY 07: TORA–5008 TODA–5008 ASDA–5008 LDA–5008
RWY 25: TORA–5008 TODA–5008 ASDA–5008 LDA–5008
SERVICE: S2 **FUEL** 100LL, JET A1+ **OX** 1, 2, 3, 4 **LGT** ACTVT REIL Rwy 07; PAPI Rwy 07 and 25; MIRL Rwy 07–25—CTAF.
NOISE: Noise sens area; use NBAA noise abatement proc; lcl ordinance rqr eng runup in dsgnd area on coml or FBO ramp fm 0400–1200Z‡ and fines.
AIRPORT REMARKS: Attended 1300–2300Z‡. Birds on and invof arpt. Aft hr Jet–A fuel—305–481–7615. Self svc fuel H24. Class I, ARFF Index A. 48 hr PPR for unsked Part 121 ops with gtr than 30 pax seats. USCBP user fee fac open Thur–Mon 1400–2230Z‡. Clsd to arrs Tues and Wed except on req and apvl by USCBP at 305–289–2029. Acft must use Twy A4 for Rwy 25 full len dep, no rwy aces byd Twy A4. 24 hr PPR for acft equipped with weather modification or geoengineering eqpt 305–289–6302. Flight Notification Service (ADCUS) avbl.
AIRPORT MANAGER: 305-289-6302
WEATHER DATA SOURCES: ASOS 135.525 (305) 743–8373.
COMMUNICATIONS: CTAF/UNICOM 122.975
Ⓡ**MIAMI CENTER APP/DEP CON** 133.5
CLEARANCE DELIVERY PHONE: For CD ctc Miami ARTCC at 305-716-1731.
RADIO AIDS TO NAVIGATION: NOTAM FILE EYW.
KEY WEST (VH) (H) VORTACW 113.5 EYW Chan 82 N24º35.15´ W81º48.03´ 077º 41.8 NM to fld. 10/1E.
VOR unusable:
063º–066º byd 40 NM
118º–124º byd 40 NM
125º–135º
136º–139º byd 40 NM
140º–220º byd 30 NM
221º–239º byd 40 NM
310º–315º byd 40 NM
TACAN AZIMUTH unusable:
125º–135º
140º–220º byd 30 NM
DME unusable:
140º–220º byd 30 NM
COMM/NAV/WEATHER REMARKS: Arpt opr notification will be transmitted on CTAF 122.975.