

MIAMI INTL (MIA)(KMIA) 8 NW UTC-5(-4DT) N25°47.72' W80°17.41'

MIAMI
H-81, L-23C, A
IAP, AD

9 B AOE Class I, ARFF Index E NOTAM FILE MIA

RWY 09-27: H13016X150 (ASPH-GRVD) S-120, D-250, 2S-175, 2D-550, 2D/2D2-1120

PCR 851 F/A/X/T HIRL CL

RWY 09: MALSR. PAPI(P4L)—GA 3.0° TCH 72'. RVR-TMR Thld dsplcd 1358'. Railroad. Rgt tfc.

RWY 27: MALSR. PAPI(P4L)—GA 3.0° TCH 71'. RVR-TMR Thld dsplcd 261'.

RWY 08R-26L: H10506X200 (ASPH-GRVD) S-120, D-250, 2S-175, 2D-550, 2D/2D2-1120 PCR 851 F/A/X/T HIRL CL

RWY 08R: MALSR. TDZL. PAPI(P4L)—GA 3.0° TCH 77'. RVR-TR

RWY 26L: MALSF. PAPI(P4L)—GA 3.0° TCH 73'. RVR-TR Rgt tfc.

RWY 12-30: H9360X150 (ASPH-GRVD) S-120, D-250, 2S-175, 2D-550, 2D/2D2-1120 PCR 780 F/A/X/T HIRL CL

RWY 12: MALSR. PAPI(P4R)—GA 3.0° TCH 72'. RVR-TR Tower.

RWY 30: MALS. PAPI(P4L)—GA 3.0° TCH 71'. RVR-TR Thld dsplcd 945'. Tree.

RWY 08L-26R: H8600X150 (ASPH-GRVD) S-120, D-250, 2D-550, 2D/2D2-1120 PCR 711 F/A/X/T HIRL CL

RWY 08L: REIL. PAPI(P4L)—GA 3.0° TCH 60'.

RWY 26R: REIL. PAPI(P4L)—GA 3.0° TCH 60'.

LAND AND HOLD—SHORT OPERATIONS

LDG RWY	HOLD—SHORT POINT	AVBL LDG DIST
RWY 09	12-30	9749
RWY 12	09-27	8100

RUNWAY DECLARED DISTANCE INFORMATION

RWY 08L:TORA-8600 TODA-8600 ASDA-8600 LDA-8600

RWY 08R:TORA-10506 TODA-10506 ASDA-10506 LDA-10506

RWY 09: TORA-13016 TODA-13016 ASDA-12755 LDA-11397

RWY 12: TORA-9355 TODA-9355 ASDA-8579 LDA-8579

RWY 26L:TORA-10506 TODA-10506 ASDA-10220 LDA-10220

RWY 26R:TORA-8600 TODA-8600 ASDA-8600 LDA-8600

RWY 27: TORA-13016 TODA-13016 ASDA-13016 LDA-12755

RWY 30: TORA-9355 TODA-9355 ASDA-8853 LDA-7913

SERVICE: S4 **FUEL** 100, JET A **OX** 1, 2, 3, 4

NOISE: All tbtj acft are reqd to use dsnt noise abatement dep profile (NADP-2) from all rwys.

AIRPORT REMARKS: Attended continuously. Birds on and invof arpt. CLOSED non-engine acft. **Rwy 08L-26R** CLOSED

0300-1200Z† when **Rwy 08R-26L** and **Rwy 09-27** are in use. **Rwy 12-30** CLOSED 0300-1200Z† when **Rwy 08R-26L** and **Rwy 09-27** are in use. Acft with a wingspan grt than 171 ft are prohibited fm tbg on Twy P east of Twy U, except ADG VI acft complying with MIA ADV VI operational plan when adj airside svc road is clsd to tfc. Acft with wingspan greater than 78' are prohibited from entering the GAC ramp. Trml apn twy spots 2, 4, 13, 15, 22, and 24 max span 125 ft or less. Trml apn twy spots 26, 28 max span 167 ft or less. PPR for inbd mil flts 100 NM on freq 130.5. All diversion ctc frequency 130.5 upon arrival. All medical emerg arr, with the exception of air ambulance flts, must secure doors until ARFF is on scene. SAID in use. Operate transponders with altitude reporting mode and ADS-B (if equipped) enabled on all airport surfaces. US CBP and EAPIS avbl. Flight Notification Service (ADCUS) avbl. Lndg Fee. 24 hr PPR for acft equipped with weather modification or geoengineering eqpt 305-876-7550.

AIRPORT MANAGER: 305-876-7038

WEATHER DATA SOURCES: ASOS 119.15 (645) 231-5974. TDWR.

COMMUNICATIONS: D-ATIS ARR 119.15 (305) 869-5445 D-ATIS DEP 133.675 (305) 869-5446 **UNICOM** 123.0

Ⓡ **APP CON** 124.85 (270°-089°) 120.5 (090°-269°) 125.75 (270°-089°) 132.025

TOWER 126.85 (270°-089°) 123.9 (090°-269°) **GND CON** 121.8 (**Rwy** 8L, 8R, 12, 26L, 26R) 127.5 (**Rwy** 09, 27, 30)

CLNC DEL 135.35 **RAMP CTL** 120.35

Ⓡ **DEP CON** 126.85 (270°-089°) 125.5 (090°-269°) 132.025

CPDLC (LOGON KUSA)

PDC

AIRSPACE: CLASS B See VFR Terminal Area Chart.

RADIO AIDS TO NAVIGATION: NOTAM FILE MIA.

DOLPHIN (VH) (H) VORTACW 113.9 DHP Chan 86 N25°48.00' W80°20.94' 099° 3.2 NM to fld. 6/4W.

TACAN AZIMUTH unusable:

055°-065° byd 35 NM blo 3,000'

185°-195° byd 23 NM

226°-236° byd 35 NM

DME unusable:

055°-065° byd 35 NM blo 3,000'

VOR unusable:

034°-037° byd 40 NM

090°-101° byd 40 NM blo 5,500'

090°-101° byd 54 NM

102°-111° byd 40 NM

LOC/DME 109.3 I-ROY Chan 30 **Rwy** 08L. LOC unusable byd 30° left of course and 25° right of course. DME unusable byd 30° left of course.

CONTINUED ON NEXT PAGE

SE, 3 SEP 2026 to 29 OCT 2026

CONTINUED FROM PRECEDING PAGE

ILS/DME 110.3 I-MFA Chan 40 Rwy 08R. Class IT. DME unusable byd 23° right of course. LOC unusable byd 20° right of course.

ILS/DME 110.9 I-BUL Chan 46 Rwy 09. Class IA.

ILS/DME 108.9 I-GEM Chan 26 Rwy 12. Class IT. Glideslope unusable byd 5° right of course; byd 6° left of course.

ILS/DME 109.1 I-VIN Chan 28 Rwy 26L. Class IE.

LOC/DME 109.3 I-CNV Chan 30 Rwy 26R.

ILS 109.5 I-MIA Rwy 27. Class IT. Autopilot cpd appch NA blw 1,200' MSL.

ILS/DME 111.7 I-DCX Chan 54 Rwy 30. Class IE.

COMM/NAV/WEATHER REMARKS: PPR 3 hrs prior to all arr on the General Aviation Center (GAC) ramp 305-876-7550 ctp Ramp Ctl and upon arr on freq 131.600.

MIAMI—OPA LOCKA EXEC (OPF)(KOPF) P (CG) 10 N UTC-5(-4DT) N25°54.45' W80°16.69' **MIAMI**
8 B LRA NOTAM FILE OPF **H-8I, L-23C, A**

RWY 09L-27R: H8002X150 (ASPH-GRVD) S-120, D-249, 2S-175, 2D-484, 2D/2D2-1000 **IAP, AD**

PCN PCN/61/F/A/W/T HIRL

RWY 09L: MALSR. PAPI(P4L)—GA 3.0° TCH 55'. Trees.

RWY 27R: MALSR. PAPI(P4L)—GA 3.0° TCH 58'. Trees. Rgt tfc.

RWY 12-30: H6800X150 (ASPH-GRVD) S-120, D-249, 2D-484, 2D/2D2-1000 PCN PCN/61/F/A/X/T HIRL

RWY 12: MALSR. PAPI(P4L)—GA 3.0° TCH 53'. Thld dsplcd 800'. Trees.

RWY 30: PAPI(P4L)—GA 3.0° TCH 52'. Tree.

RWY 09R-27L: H4309X100 (ASPH-GRVD) S-96, D-154 PCN PCN/36/F/A/Y/T MIRL

RWY 09R: VASI(V4L)—GA 3.0° TCH 26'. Pole. Rgt tfc.

RWY 27L: PAPI(P4L)—GA 3.5° TCH 52'. Trees.

RUNWAY DECLARED DISTANCE INFORMATION

RWY 09L:TORA-8002 TODA-8202 ASDA-8202 LDA-8002

RWY 09R:TORA-4306 TODA-4306 ASDA-4306 LDA-4306

RWY 12:TORA-6800 TODA-7800 ASDA-7000 LDA-6000

RWY 27L:TORA-4306 TODA-4306 ASDA-4306 LDA-4306

RWY 27R:TORA-8002 TODA-8202 ASDA-8202 LDA-8002

RWY 30:TORA-6800 TODA-7000 ASDA-7000 LDA-6800

SERVICE: S4 **FUEL** 100LL, JET A **OX** 1, 2, 3, 4 **LGT** When ATCT cisd ACTVT MALSR Rwy 12; PAPI Rwy 12 and 30; HIRL Rwy 12-30—CTAF. 30 min PPR to req actvn of MALSR Rwy 09L; MALSR Rwy 27R; PAPI Rwy 09L and 27R; HIRL Rwy 09L-27R—305-869-1660 and CTAF. Rwy 09L: PAPI unusbl byd 7 degs R of cntrln. **MILITARY—FUEL** J5 (PPR CG) A+ (C305-687-8410.) (NC-100LL, A) Contract fuel—305-685-4646. **FLUID** LHGX

NOISE: Noise sensitive arpt. Flt T is ltd to acft 40,000 lbs max gross tkof wt and blw & only btn 1200-0400Z†. Specific tfc pats are published for hel and fixed wing tfc; compliance is mandatory. Obtain info fm ATCT or FBO or amgr; or req specific tfc pat instructions on initial etc. Rwy 09R-27L cisd dly 0400-1200Z† for acft noise abatement to smrdg arpt community.

AIRPORT REMARKS: Attended continuously. Birds invof arpt. Dual tfc pats for hels and fixed wing acft in use Rwy 09R-27L. Acft with wingspans gr than 117' are prohibited fm txig on Twy P btn Twy H and Twy N8. Hel arr and dep avoid flying over parked or try acft. All acft and vehicles should rpt psns to ATC by using the sfc painted spot nrs on all exits to the ramp and non-movement areas. Vehicle lane xing Twy E to the fire stn is non-movement. Twy C and B south of Twy P are non-movement areas. Twy T btn Twy E and Twy T8 rcdcd spd rqrd for acft wingspan more than 117'. Twy R btn Twy F and G strtd to acft with wingspan less than 94'. 24 hr PPR for acft equipped with weather modification or geoeengineering eqpt 305-869-1660. Flt Notification Svc (ADCUS) avbl 1300-0400Z†. NOTE: See Special Notices—Arrival Alert.

AIRPORT MANAGER: 305-869-1662

WEATHER DATA SOURCES: ASOS 125.9 (305) 681-4063. LAWRS.

COMMUNICATIONS: CTAF 134.675 **ATIS** 125.9

® **APP/DEP CON** 128.6

TOWER 134.675 (1200-0400Z†) **GND CON** 120.025 **CLNC DEL** 119.2

GCO 119.45)

CLEARANCE DELIVERY PHONE: For CD, if una via GCO, ctc Miami Apch at 305-869-5432.

AIRSPACE: CLASS D svc 1200-0400Z†; other times CLASS G.

RADIO AIDS TO NAVIGATION: NOTAM FILE MIA.

DOLPHIN (VH) (H) VORTACW 113.9 DHP Chan 86 N25°48.00' W80°20.94' 035° 7.5 NM to fld. 6/4W.

TACAN AZIMUTH unusable:

055°-065° byd 35 NM blo 3,000'

185°-195° byd 23 NM

226°-236° byd 35 NM

DME unusable:

055°-065° byd 35 NM blo 3,000'

VOR unusable:

034°-037° byd 40 NM

090°-101° byd 40 NM blo 5,500'

090°-101° byd 54 NM

102°-111° byd 40 NM

CONTINUED ON NEXT PAGE